



ECOBLOC SMART ATTENUATION



NB. The attenuation tank must be vented to a suitable location above ground and it is recommended to have one Ø100mm vent pipe for every 7,500m² of impermeable catchment area. For recommendation on venting size, please contact GRAF Australia.

THIS DOCUMENT IS SUPPLIED IN STRICT CONFIDENCE AND MUST NOT BE LENT, REPRODUCED OR DISCLOSED TO ANY THIRD PARTY WITHOUT THE WRITTEN CONSENT OF GRAF AUSTRALIA PTY LTD


DO NOT SCALE - IF IN DOUBT ASK

Notice: This drawing is issued only as a guideline and is an estimate of the materials required to construct the drainage system, it should not be used for construction purposes.
Graf Australia Pty Ltd makes no warranty or guarantee in relation to the suitability of any of the layout details shown on this drawing in relation to a particular scheme.


- NOTES:-
- All dimensions in mm, unless otherwise stated.
 - All dimensions are nominal and may vary within manufacturing tolerances.
 - All site temporary enabling works by others.
 - Graf products to be installed in strict accordance with Graf recommendations.
 - This drawing is intended for guidance only. Confirmation of the suitability for a particular project should be sought from the consulting engineers prior to final design or commencement of any construction works.

Maximum pipe connections depending on the depth of the system as well as the Vario Shaft components. Maximum connection in the Vario Shaft is 420mm outside diameter. Adaptor plates can be supplied to suit the specific job for connections over 225mm and it requires minimum 2 layers of Ecoblocs, with maximum connections of 600mm outside diameter.


ECOBLOC SMART



	Ecobloc	Baseplate
Dimensions (mm)	800 x 800 x 330	800 x 800 x 40
Gross Volume (m ³)	0.211m ³	0.025m ³
Net Volume (m ³)	0.202m ³	0.024m ³
Material	Polypropylene	Polypropylene
Weight	9.9kg	4.2kg
Void Ratio	>96% depending on number of layers	
Inspectable	Yes	
Comply to load requirements of AS5100		



NOTE: EXCAVATION TO EXCEED TANK SIZE BY 500MM ON ALL SIDES TO ALLOW FOR ACCESS. IF THERE IS ANY GROUND WATER CONDITIONS TO BE CONSIDERED PLEASE CONTACT GRAF TECHNICAL TEAM.



* These values depends on installation conditions. Please, contact GRAF Technical team for more details.

2	LATEST REVISION	AA	05.01.2023
1	LATEST REVISION	MV	15.09.2022
REV.	DESCRIPTION	BY	DATE

GRAF GRAF Australia Pty Ltd

GRAF Australia Pty Ltd, 43b Sparks Road (rear building), Henderson 6166 WA

T: +61 1300 131 971 F: +61 8 6499 2688

E: info@grafaustalia.com.au www.grafaustalia.com.au

DRAWN :	AA	DATE :	05.01.2023
CHECKED :	MV	SCALE :	VARIOUS@A3

PROJECT

GRAF STANDARD DETAILS

DESCRIPTION

ATTENUATION TANK using GRAF ECOBLOC SMART & VARIO SHAFT




DRAWING No. **DWG-359** REV. **2** (Pg.1)

THIS DOCUMENT IS SUPPLIED IN STRICT CONFIDENCE AND MUST NOT BE LENT, REPRODUCED OR DISCLOSED TO ANY THIRD PARTY WITHOUT THE WRITTEN CONSENT OF GRAF AUSTRALIA PTY LTD




DO NOT SCALE - IF IN DOUBT ASK

Notice: This drawing is issued only as a guideline and is an estimate of the materials required to construct the drainage system, it should not be used for construction purposes.

Graf Australia Pty Ltd makes no warranty or guarantee in relation to the suitability of any of the layout details shown on this drawing in relation to a particular scheme.




Geomembranes and Geotextiles with characteristics less than those specified are unlikely to be suitable and are therefore not recommended for use with Graf Australia systems for this application




Place the Baseplates on the inner geotextile layer followed by the first layer of EcoBlocs securing them with connectors. Make sure the Vario shaft is the correct position for inspection.

After all layers of EcoBlocs and the Vario shaft are placed and secure, install the EndPlates. Endplates are clipped to the tank where it is required.

Place the one layer of EcoBlocs on top of the previously placed layer ensuring the connector are clipped locking the EcoBlocs together.




Connector clips are Red for illustration purposes only and are Grey in colour




- INSTALLATION METHOD:**
- Excavate the trench with a safe batter (or stepped) ensuring the footprint allows for sufficient space between tank and the sides (minimum 500mm around all sides of the tank).
 - Mark out the position of the tank including inlets and outlets.
 - Lay min. 50mm of single sized non angular stone (8 to 16mm) as a base for the tank. This can be laid to a maximum fall of 1°.
 - Lay the outer geotextile over the base of the excavation and up the sides of the trench, overlapping any joins by a minimum of 300mm.
 - Lay the geomembrane on top of the outer geotextile.
 - Geomembrane must be joined by thermal fusion heated wedge welding by an experienced operator that holds an appropriate National Qualification or other qualification for membrane installation. It is recommended that the Dual Seam method is used as this generates an unwelded channel which can be pressured with air to check the integrity of the weld.
 - Lay the inner geotextile over the geomembrane before starting to build the tank.
 - The geomembrane and geotextile used must meet the specification stated on the drawing.
 - Place EcoBlocs Smart Baseplates onto the inner of the geotextile, according to inspection orientation. Baseplates do not require clipping. If a Vario shaft is to be included within the tank make sure the Vario shaft base is in position located (Vario shaft base do not require a EcoBloc baseplate).
 - Place EcoBlocs Smart on the baseplates according to inspection orientation, position leg ends into corresponding holes in the Baseplate. The bloc will only fit in the correct orientation. Push down firmly to ensure the EcoBloc is located correctly, clipping each adjacent bloc using the connectors until the first layer is completed.
 - Make sure the row of EcoBlocs Smart are in the correct located position where inspection run is required.
 - To install the next layer of blocs remove from the stack and turn 90° and position directly above the bloc below. Push down firmly to ensure the bloc is located correctly.
 - Continue until all EcoBlocs Smart have been installed, ensuring clips are used to secure each bloc.
 - Fit Endplates to the sides of each bloc by positioning the bottom in place then pushing firmly on the top section to locate into place.
 - Fix adaptor plates to the sides of the blocs in the required position for the inlet and outlet pipes if required.
 - Cut a hole in the geomembrane and geotextile for inlet and outlet connections.
 - Pull geomembrane up around the sides and fully wrap the blocs, securing the top in place by heated wedge welding to the side panels.
 - Cover the top and sides with the outer geotextile to protect the geomembrane.
 - Install vent pipe connection into the top of the tank at a suitable location.
 - Backfill around the tank in 300mm layers increments using non-cohesive, compressible loose rock (gravel, crushed rock, sand, etc).
 - Connect inlet/outlet pipes and weld/glue them to have a watertight connection.
 - In order to prevent silt from entering the tank it is recommended that silt traps or catchpit manholes are installed upstream of any inlet. These should be regularly maintained to avoid the buildup of any silt.
- N.B. Installation method may vary depending on depth of the tank and is project specific. For more information or technical questions please contact our Technical Department at Graf Australia.

2	LATEST REVISION	MV	05.01.2023
1	LATEST REVISION	MV	15.09.2022
REV.	DESCRIPTION	BY	DATE



Finally, wrap the blocs with the inner geotextile followed by the geomembrane ensuring it is heat welded then wrap with the outer geotextile to protect the membrane. Geomembrane must be joined by an experienced operator that holds an appropriate National Qualification or other qualification for membrane installation.



GRAF GRAF Australia Pty Ltd

GRAF Australia Pty Ltd, 43b Sparks Road (rear building), Henderson 6166 WA
T: +61 1300 131 971 F: +61 8 6499 2688
E: info@grafaustalia.com.au www.grafaustalia.com.au

DRAWN : AA DATE : 05.01.2023
CHECKED : MV SCALE : VARIOUS@A3

PROJECT
GRAF STANDARD DETAILS

DESCRIPTION
**ATTENUATION TANK
using GRAF ECOBLOC SMART &
VARIO SHAFT**

DRAWING No. **DWG-359** REV. **2**
(Pg.2)

THIS DOCUMENT IS SUPPLIED IN STRICT CONFIDENCE AND MUST NOT BE LENT, REPRODUCED OR DISCLOSED TO ANY THIRD PARTY WITHOUT THE WRITTEN CONSENT OF GRAF AUSTRALIA PTY LTD

DO NOT SCALE - IF IN DOUBT ASK

Notice: This drawing is issued only as a guideline and is an estimate of the materials required to construct the drainage system, it should not be used for construction purposes.

Graf Australia Pty Ltd makes no warranty or guarantee in relation to the suitability of any of the layout details shown on this drawing in relation to a particular scheme.

NOTES:-

1. All dimensions in mm, unless otherwise stated.
2. All dimensions are nominal and may vary within manufacturing tolerances.
3. All site temporary enabling works by others.
4. Graf products to be installed in strict accordance with Graf recommendations.
5. This drawing is intended for guidance only. Confirmation of the suitability for a particular project should be sought from the consulting engineers prior to final design or commencement of any construction works.

VARIO 800 TYPE 1


Dimensions (mm) 800 x 800 x 355
Weight 14kg
Volume 230 (litres)

VARIO 800 TYPE 2

Dimensions (mm) 800 x 800 x 660
Weight 24kg
Volume 420 (litres)

VARIO 800 BASE/COVER SET

Dimensions (mm) 800 x 800 x 100
Weight 11kg



EXTERNAL VIEW

INTERNAL VIEW

2	LATEST REVISION	AA	05.01.2023
1	LATEST REVISION	MV	15.09.2022
REV.	DESCRIPTION	BY	DATE



GRAF GRAF Australia Pty Ltd
 GRAF Australia Pty Ltd, 43b Sparks Road (rear building), Henderson 6166 WA
 T: +61 1300 131 971 F: +61 8 6499 2688
 E: info@grafaustalia.com.au www.grafaustalia.com.au

DRAWN : AA	DATE : 05.01.2023
CHECKED : MV	SCALE : VARIOUS@A3


PROJECT
GRAF STANDARD DETAILS

DESCRIPTION
**ATTENUATION TANK
using GRAF ECOBLOC SMART &
VARIO SHAFT**

DRAWING No.	REV.
DWG-359	2
	(Pg.3)



Vario 800 flex, type 1
Do not drill or use for inspection



Vario 800 flex, type 2
Drill DN400 on the mark towards the Ecobloc to access the tank for inspection



Vario 800 are modular and are easily assembled in a push fit manner.