
3.24 | DRAINAGE | D16.18 BRIO 700MM LOCKING ACCESS COVER AND FRAME

Brio 700mm Locking Access Cover and Frame

Technical Guide D16.18

Large Bolt Down Access Cover and Frame where security and a larger opening is required.



Applications

Transport hubs

Parking areas, streets, and hard shoulders

Water and Wastewater networks

Security applications

Product Attributes

Minimum 700mm clear opening for maneuverability

Has a hinged cover for ergonomic opening

Has a locked retractable handle

Can accommodate field staff wearing breathing apparatus

Approvals/Standards

AS3996:2019 Class D240kN

P5 rated for slip resistance to AS4586:2013

Quality

Manufactured from Ductile Iron grade 500/7, in accordance with ISO 1083



The Brio 700mm is a high quality long serving Ductile Iron bolt down cover and frame system manufactured to the highest standards in Europe. These covers offer security and are the perfect solution where a larger opening is required.

Features


- Brio 700 covers are machine moulded in Europe.
- Polyethylene elastic support to eliminate the risk of traffic noise.
- Seatings ensure non-rock stability.
- Has a hinged cover for ergonomic opening.
- Cover has five guides to ensure central positioning.
- Secured retractable handle is locked by a coded screw/nut system.
- Unlocking with coded key.
- Cover can be removed from the 90° angle.
- Cover opening angle is 120° angle.
- Nontoxic water based black painted coating.


Dimensions

- Clear Opening 700mm
- Cover External Diameter- 750mm
- Overall Dimension 1000mm
- Depth of frame 100mm
- Cover Weight: 48kg
- Total Weight: 80kg

Product Code	Description
DIMHBCF700H	Brio Access Cover Ø700 Locking
DIMHLK	Locking Key for Access Covers







Branches Nationwide Support Office & Technical Services 0800 93 7473

Disclaimer: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hynds product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hynds unless expressly stated in any sale and purchase agreement entered into between Hynds and the user.

